

PRODUCT SPECIFICATION

CDTECH Model: **S063BWV01HN-FC01**

CUSTOMER Model: **-**

Description: **6.3 " TFT-LCD Module with CTP**

Version: **1.0**

CDTECH	PREPARED BY	CHECKED BY	APPROVED BY
SIGNATURE	罗洪飞	洪晓仪	黄丽
DATE	2023.12.18	2023.12.18	2023.12.18

CUSTOMER APPROVAL	SIGNATURE	DATE



Record of Revisions

[illegible]



Contents

1. General Specifications	4
2. Absolute Maximum Ratings	5
3. Electrical Characteristics	5
4. Interface Pin Assignment	7
5. Interface Characteristics	8
6. Optical Specifications	14
7. Reliability Test Items	17
8. Mechanical Drawing	18
9. Packing	19
10. Precautions for Use of LCD modules	20

1. General Specifications

1.1 LCM General Information

Item	Specification	Unit
LCD Size	6.3	inch
Number of Pixels	800 (H) RGB x 280 (V)	pixels
Display Mode	Normally Black	-
Viewing Direction	Free	o' clock
Interface	RGB	-
Display Colors	262K	colors
Outline Dimension	166.20 (H) x 68.20 (V) x 7.23 (D)	mm
Active Area	150.00 (H) x 52.50 (V)	mm
Pixel Pitch	0.1875 (H) x 0.1875 (V)	mm
Driver IC	HX8272	-
Operation Temperature	-20~70	°C
Storage Temperature	-30~80	°C

1.2 Touch Panel Information

Item	Specification
Touch Structure	G+G
Bonding Type with LCM	OCA Optical Bonding
Driver IC	MXT640T
Interface	I ² C
Touch Count Max	5 Points
Surface treatment	-
Surface hardness	6H
I2C slave address	0x4A
Origin of coordinate	Top Left Corner

Note1: Requirements on environmental protection RoHS compliant.

2. Absolute Maximum Ratings

Item	Symbol	MIN.	MAX.	Unit	Note
Analog Supply voltage	VDD	-0.3	5.0	V	Note 1

Note 1: Permanent damage may occur to the LCD module if beyond this specification.

Functional operation should be restricted to the conditions described under normal operating conditions.

3. Electrical Characteristics

3.1 Recommended Operating Condition for TFT LCD


Item	Symbol	Min.	Typ.	Max.	Unit	Note
Analog Supply voltage	VDD	3.0	3.3	3.6	V	
Analog supply current	I _{VDD}	-	TBD	-	mA	VDD=3.3V
Logic input voltage	V _{IH}	0.7*VDD	-	VDD	V	
	V _{IL}	GND	-	0.3*VDD	V	

3.2 Recommended Driving Condition for Backlight

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Driving Current	I _F	-	150	-	mA	
Driving Voltage	V _F	8.1	-	10.2	V	
Power consumption	W _{BL}	1.215	-	1.53	W	
LED Life-Time	N/A	-	50,000	-	Hours	Ta=25°C Note 1


Note 1: LED lifetime is defined as the module brightness decay 50% of original brightness at Ta=25 degree, typical current.

Note 2:LED circuit :



CIRCUIT DIAGRAM

3.3 Forward current derating curve vs. Ambient temperature



3.4 Touch Panel

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Power Supply voltage	VDD	-	3.3	-	V	
Analog supply current	I_{VDD}	-	TBD	-	mA	VDD=3.3V
Input high-level voltage	V_{IH}	$0.7 \cdot VDD$	-	VDD	V	
Input low -level voltage	V_{IL}	GND	-	$0.3 \cdot VDD$	V	

4. Interface Pin Assignment

4.1 LCM Pin Assignment

No.	Symbol	Description
1	VBL-	Power for LED backlight (Cathode)
2	VBL+	Power for LED backlight (Anode)
3	GND	Ground
4	VDD	Power supply
5-12	R0-R7	Data bus
13-20	G0-G7	Data bus
21-28	B0-B7	Data bus
29	GND	Ground
30	DCLK	Dot clock signal input. Latching input data at its rising edge
31	DISP	Standby mode.active low. DISP="1": Normally operation (Default) DISP="0": Timing controller,output buffer,DAC and power circuit all off
32	HSYNC	Horizontal sync input. Negative polarity
33	VSYNC	Vertical sync input. Negative polarity
34	DE	Data enable input. Active high to enable the input data bus under "DE Mode"
35	NC	No connection
36	GND	Ground
37	NC	No connection
38	NC	No connection
39	NC	No connection
40	NC	No connection


4.2 Touch FPC Pin Assignment

No.	Symbol	Description
1	GND	Ground
2	SDA	I2C data input and output for CTP
3	SCL	I2C clock input for CTP
4	VDD	Power supply for CTP
5	INT	Interrupt signal for CTP
6	XRES	Reset Pin for CTP

5. Interface Characteristics

5.1 POWER ON/OFF SEQUENCE

5.1.1 Power On Sequence



5.1.2 Power Off Sequence



5.2 RGB Interface

5.2.1 SYNC Mode

Horizontal




Figure 6.8: Horizontal input timing at Sync mode

Vertical




Figure 6.9: Vertical input timing at Sync mode

Parameter	Symbol	Panel Resolution			Unit
		800×RGB×280			
		Min.	Typ.	Max.	
DCLK frequency	F _{DCLK}	20	30	40	MHz
Horizontal valid data	T _{hd}	800			DCLK
Hsync pulse Width	T _{hpw}	1	9	29	DCLK
Hsync back porch	T _{hbp}	1	6	26	DCLK
Hsync front porch	T _{hfp}	30	50	70	DCLK
1 horizontal line	t _h	831	856	896	DCLK
Vertical valid data	T _{vd}	280			H
Vsync pulse Width	T _{vpw}	1	4	24	H
Vsync back porch	T _{vbp}	1	21	41	H
Vsync front porch	T _{vfp}	1	16	36	H
1 Vertical field	t _v	282	317	357	H
Frame rate	FR	-	60	-	Hz

5.3 RGB mode AC electrical characteristics




Figure 9.7: Input signal timing

Input data/Sync. parameters

(VCC1=VCC1P=VCC2=VCCIF=3.0V to 3.6V, VSS1=VSS2=VSSA=0V, T_A=-30~85°C)

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
DCLK period	t _{CPH}	16.67	-	-	ns
DCLK clock high/low width	t _{CW}	6	-	-	ns
Data setup time	t _{DSU}	5	-	-	ns
Data hold time	t _{DHD}	5	-	-	ns
VS/HS/DE setup time	t _{SS}	5	-	-	ns
VS/HS/DE hold time	t _{SH}	5	-	-	ns
Input signal rising time	t _R	-	-	10	ns
Input signal falling time	t _F	-	-	10	ns

5.4 Reset timing




Figure 9.8: Reset timing

(VCC1=VCC1P=VCC2=VCCIF=3.0V to 3.6V, VSS1=VSS2=VSSA=0V, $T_A=-30\sim85^{\circ}\text{C}$)


Signal	Parameter	Symbol	Spec.			Unit
			Min.	Typ.	Max.	
RESETB	Reset pulse width	tRW	10	-	-	μs
	Reset complete time	tRT	-	-	5	μs
	Positive spike noise width	tPNS	-	-	100	ns
	Negative spike noise width	tNNS	-	-	100	ns

6. Optical Specifications

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Viewing Angle (CR≥10) B/L ON	θ_T	$\Phi=90^\circ$ (12 o'clock)	80	85	-	deg	Note2
	θ_B	$\Phi=270^\circ$ (6 o'clock)	80	85	-	deg	Note2
	θ_L	$\Phi=180^\circ$ (9 o'clock)	80	85	-	deg	Note2
	θ_R	$\Phi=0^\circ$ (3 o'clock)	80	85	-	deg	Note2
Response Time	T_{ON}	Normal $\theta=\Phi=0^\circ$	-	15	17	msec	Note4
	T_{OFF}		-	15	17	msec	Note4
Contrast Ratio	CR		300	600	-	-	Note1 Note3
Color Chromaticity	W_X		0.264	0.294	0.324	-	Note1 Note5
	W_Y		0.288	0.318	0.348	-	Note1 Note5
Luminance	L		400	500	-	cd/m ²	Note1 Note7
Luminance Uniformity	Y_U		75	80	-	%	Note1 Note6
NTSC	-		50	55	-	%	-

Note 1:Definition of optical measurement system

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note 2: Definition of viewing angle range and measurement system

Viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).





Fig. 1 Definition of viewing angle

Note 3: Definition of contrast ratio

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

The luminance uniformity in surface luminance is determined by measuring luminance at each test position 1 through n, and then dividing the maximum luminance of n points luminance by minimum luminance of n points luminance. For more information see FIG.2




Fig. 2 Definition of points

Note 7: Definition of Luminance (Refer Fig. 2)

Surface luminance is the luminance with all pixels displaying white.

L_v = Average Surface Luminance with all white pixels($P_1, P_2, P_3, \dots, P_n$).


7. Reliability Test Items

Test Item	Test Conditions
High Temperature Storage	Ta= +80℃ 96hrs
Low Temperature Storage	Ta= -30℃ 96hrs
High Temperature Operation	Ta= +70℃ 96hrs
Low Temperature Operation	Ta= -20℃ 96hrs
High Temperature and Humidity Storage	Ta= +60℃, 90% RH 96hrs
Thermal Shock (Non-operation)	-30℃/30 min ~ +80℃/30 min for 20 cycles Start with cold temperature end with high temperature
Electro Static Discharge	Contact = ± 4 kV, class B Air = ± 8 kV, class B R=330Ω,C=150pF
Vibration	Sweep: 10Hz~55Hz~10Hz Stroke: 1.5mm 2 hrs for each direction of X .Y. Z.
Mechanical Shock	60G 6ms,±X,±Y,±Z 3 times for each direction
Package Drop Test	Height: 60 cm 1 corner, 3 edges, 6 surfaces


Notes: The test result shall be evaluated after the sample has been left at room temperature and humidity for 2 hours without load. No condensation shall be accepted. The sample will not be accepted if appear these defects:

- 1). Air bubble in the LCD
- 2). Seal leak or Glass crack
- 3). Non display or abnormal display
- 4). Brightness reduction >50%

8. Mechanical Drawing



9. Packing



10. Precautions for Use of LCD modules

10.1 Handling Precautions

10.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

10.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

10.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

10.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

10.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketene
- Aromatic solvents

10.1.6. Do not attempt to disassemble the LCD Module.

10.1.7. If the logic circuit power is off, do not apply the input signals.

10.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1. Be sure to ground the body when handling the LCD Modules.

10.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

10.2 Storage Precautions

10.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

10.2.2. The LCD modules should be stored under the storage temperature range if the LCD modules will be stored for a long time, the recommend condition is :

Temperature : 0℃ ~40℃ Relatively humidity: ≤80%

10.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

10.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.